```
ANSWER 104 OF 161 CA COPYRIGHT 2005 ACS on STN
L3
    115:261881 CA
AN
    Entered STN: 14 Dec 1991
ED
    Ceramic binding compositions and method for binding ceramics
ΤI
    Natsui, Tetsuaki
IN
    Asahi Glass Co., Ltd., Japan
PΑ
    Jpn. Kokai Tokkyo Koho, 12 pp.
SO
    CODEN: JKXXAF
DT
    Patent
LΑ
    Japanese
    ICM C09J001-02
IC
    ICS C03C014-00; C09J005-00; C09J005-06
CC
    57-2 (Ceramics)
    Section cross-reference(s): 47
FAN.CNT 1
                                         APPLICATION NO. DATE
    PATENT NO. KIND DATE APPLICATION NO. DATE

JP 03192176 A2 19910822 JP 1989-329722 19891221

JP 2734147 B2 19980330
    JP 03192176
PRAI JP 1989-329722
                             19891221
CLASS
             CLASS PATENT FAMILY CLASSIFICATION CODES
 PATENT NO.
 JP 03192176 ICM C09J001-02
               ICS C03C014-00; C09J005-00; C09J005-06
    The compns. comprise binding component 10-50, and ceramic aggregate (e.g.,
AΒ
    cordierite) 50-90 weight parts. The binding component contains
    alkali metal silicate (mainly water glass)
    80-85, and amorphous silica powder (particle diameter \leq 0.1~\mu m) 5-20
    weight%. Addnl., appropriate amount of water is added to the composition
    to form a paste having viscosity 103-106 P at shear strength 10 s-1 for
    joining. The binding ia carries out by filling the composition in the seam
     (0.5-5 mm) of 2 adjacent ceramic members (e.g., porous cordierite
     filter plates), and heating at 400-1200° for hardening.
    Optionally, the composition can be pre-extruded to form sheet shapes, then
    arranged in the seam for joining.
ST
    binding compn ceramic water glass; cordierite filter
    plate binding compn
```

(binding of, to ceramics, water glass-amorphous silica-based

binders containing ceramic aggregates for)

(cordierite, binders for, compns. of water

IT

ΙT

Ceramic materials and wares

Filters and Filtration apparatus

glass-amorphous silica-based)